



**Specification**

**DR CW602 Brass Ball Valves Screwed BSP  
Dual Approved Water Mark and AGA**

**Pressure / Temperature**

**Max Pressure Rating 2500 kpa (water)**

**Working Temperature Water : 0 to 90 deg C / Air : 15 to 90 deg C / Gas : 15 to 60 deg c**

**DUAL APPROVED**

**Watermark Approval to : MP52 Spec 012 approval number 20042**

**Material List**

1. BODY	CW602 BRASS
2. BODY CAP	CW602 BRASS
3. SEAT	P T F E
4. BALL	CW602 BRASS

5. STEM	CW602 BRASS
6. STEM PACKING	NBR
7. COMP NUT	CU2
8. LEVER	Stainless Steel 304

**Valve Dimensions**

Size	mm	15	20	25	32	40	50
	inch	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
L		92	92	105	134	134	144
H		45	50	56	73	78	93
W		60	67	76	93	101	122



**MATTHEW DAVIS Australia P/L**

102 - 104 Malcolm Road, Braeside, Victoria, 3195

Telephone: (03) 9580 0066 Facsimile: (03) 9587 2829

Web: [www.matthewdavis.com.au](http://www.matthewdavis.com.au) Email: [sales1@matthewdavis.com.au](mailto:sales1@matthewdavis.com.au)